



#### Material

Body: stainless steel (AISI 304) Race: steel/ bronze - PTFE composite. Inner ring: stainless steel, hardened and ground (AISI 304). Outer ring: brass body pressed around, outer race lined with bronze - PTFE compo-

## site.

Joint ball: stainless steel (AISI 440C)

#### **Technical Notes**

Maintenance free. Sizes according to DIN ISO 12740-4, series K

#### Tips

Standard thread is right hand thread. Rod end studs are all right hand threads.

#### **Important Notes**

\*denotes fine pitch threads.

Order No.	Thread hand	d <sub>1</sub>	d <sub>2</sub>	1 <sub>1</sub>	$w_1$	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	1 <sub>2</sub>	Weight
R3613 R006	Right	M6	M6	30	9	20	100	13	90	12	22
R3613 R008	Right	M8	M8	36	12	24	12.5	16	10.5	16	47
R3613 R010	Right	M10	M10	43	14	28	15.0	19	13.0	20	77
R3613 R011	Right	M10 x 1 25*	M10	43	14	28	15.0	19	13.0	20	100
R3613 R012	Right	M12	M12	50	16	32	17.5	22	15.0	22	100
R3613 R013	Right	M12 x 1 25*	M12	50	16	32	17.5	22	15.0	22	100
R3613 R014	Right	M12 X 1,20	M14	57	19	36	20.0	25	17.0	25	160
R3613.R015	Right	M14 x 1.5*	M14	57	19	36	20.0	25	17.0	25	160
R3613.R016	Right	M16	M16	64	21	42	22.0	27	19.0	28	220
R3613.R017	Right	M16 x 1.5*	M16	64	21	42	22.0	27	19.0	28	220
R3613.L006	Left	M6	M6	30	9	20	10.0	13	9.0	12	22
R3613.L008	Left	M8	M8	36	12	24	12.5	16	10.5	16	47
R3613.L010	Left	M10	M10	43	14	28	15.0	19	13.0	20	77
R3613.L011	Left	M10 x 1,25*	M10	43	14	28	15.0	19	13.0	20	100
R3613.L012	Left	M12	M12	50	16	32	17.5	22	15.0	22	100
R3613.L013	Left	M12 x 1,25*	M12	50	16	32	17.5	22	15.0	22	100
R3613.L014	Left	M14	M14	57	19	36	20.0	25	17.0	25	160
R3613.L015	Left	M14 x 1,50*	M14	57	19	36	20.0	25	17.0	25	160
R3613.L016	Left	M16	M16	64	21	42	22.0	27	19.0	28	220
R3613.L017	Left	M16 x 1,50*	M16	64	21	42	22.0	27	19.0	28	220
									а	Static	load C <sub>o</sub>
Order No.	I <sub>3</sub>	۱ <sub>4</sub>	1 <sub>5</sub>	w <sub>2</sub>		A/F <sub>1</sub>	A/F <sub>2</sub>		0	k	N.
										m	ax.
R3613.R006	18.5	13	10	6.75		11	8		13	7	.7
R3613.R008	23.5	17	13	9.00		14	8		14	12	2.9
R3613.R010	28.0	21	17	10.50		17	12		13	18	3.0
R3613.R011	28.0	21	17	10.50		17	12		13	18	3.0
R3613.R012	32.5	25	20	12.00		19	14		13	24	4.0
R3613.R013	32.5	25	20	12.00		19	14		13	24	4.0



# Rod Ends

# Stainless Rod End with Stud



Order No.	I <sub>3</sub>	I <sub>4</sub>	I <sub>5</sub>	w <sub>2</sub>	$A/F_1$	A/F <sub>2</sub>	a °	Static load C <sub>o</sub> kN max.
R3613.R014	37.5	29	22	13.50	22	14	16	31.0
R3613.R015	37.5	29	22	13.50	22	14	16	31.0
R3613.R016	42.5	33	24	15.00	22	17	15	39.0
R3613.R017	42.5	33	24	15.00	22	17	15	39.0
R3613.L006	18.5	13	10	6.75	11	8	13	7.7
R3613.L008	23.5	17	13	9.00	14	8	14	12.9
R3613.L010	28.0	21	17	10.50	17	12	13	18.0
R3613.L011	28.0	21	17	10.50	17	12	13	18.0
R3613.L012	32.5	25	20	12.00	19	14	13	24.0
R3613.L013	32.5	25	20	12.00	19	14	13	24.0
R3613.L014	37.5	29	22	13.50	22	14	16	31.0
R3613.L015	37.5	29	22	13.50	22	14	16	31.0
R3613.L016	42.5	33	24	15.00	22	17	15	39.0
R3613.L017	42.5	33	24	15.00	22	17	15	39.0

Automotion AN ESSENTRA COMPANY



# **Technical Information**

Rod Ends Introduction

All of our rod ends incorporate either a plain spherical bearing, ball bearing, or roller bearing. Below is an overview of each type.

#### Plain spherical bearings



#### Ball and roller bearings



- A Radial clearance: 10-30µm, low friction
- **B** Inner ring made of bearing steel, hardened ball grooves polished
- **C** Shields on both sides protect against rough dirt penetration
- **D** All rod ends housings are made of forged steel, case hardened bearing race
- **E** Low maintenance due to long-term greasing, especially suitable for high speed large swiveling angles or rotating movements

#### Rod ends and water



#### Stainless steel versions

Most of our rod ends are available in stainless steel as standard

High grade AISI 316 stainless steel available on request

Ends from Automotion Compone





Rod End



ov-rod-ends-bearings-lnh- Updated - 28-03-2023

#### Rod ends with integral maintenance-free spherical plain bearings

In many cases heavy-duty rod ends with integral spherical plain bearings are most often used. They are above all used for small swivelling or tilting movements at low speeds. They stand out for their high load capacity and can also be used for shock-like loads. The rod end ball slides on a plastic bearing shell consisting of a glass fibre-filled nylon/teflon compound. This design assures a maintenance-free rod end. Heavy-duty plain bearing rod ends have slight initial movement friction and virtually no clearance. The plastic material used has another advantage in that it can absorb many foreign particles so that no damage can occur. The balls of heavy-duty rod ends with integral spherical plain bearings are hard chrome plated. This reliable corrosion protection ensures that the function of the rod end will not be affected by a corroded ball surface under humid operating conditions.

#### Rod ends with integral ball bearings

This design is especially suitable for high speeds, large swivelling angles or rotating movements with relatively low or medium loads. Prominent technical features are the low bearing friction, long-time greasing as well as the sealing against some dirt penetration (by means of shields on both sides). Under normal operating conditions the rod ends are maintenance-free.

Greasing nipples are provided for lubrication in case of rough operations and maximum loads. To avoid incompatibility with the production lubrication, we recommend lubrication with a calcium-complex-soap-grease. A special heat treatment procedure gives the rod end housing a raceway hardness adapted to the antifriction bearing, ensuring at the same time high stability with changing loads.

#### Rod ends with integral roller bearings

This design based on the structure of a self-aligning roller bearing is preferably used for high speed, large tilting angles or rotating movements under high loads. Compared to rod ends with ball bearings, rod ends with self-aligning roller bearings have essentially higher basic load ratings. This design is equipped with a cage to minimise the rolling friction and heat build-up. These rod ends, with long-time lubrication are under normal operating conditions maintenance-free.

Greasing nipples are provided for lubrication in case of rough operations and maximum loads. To avoid incompatibility with the production lubrication, we recommend lubricating with a calcium-complex-soap-grease.

Shields on both sides limit dirt particles from penetrating into the bearing. The rod ends with roller bearings are, subjected to a special heat treatment to obtain a raceway hardness adapted to the antifriction bearings, ensuring at the same time a high stability with changing loads.





# Technical Information

Rod End Bearings Load Capacity Explained



#### Static load capacity C<sub>0</sub> (plain bearings)

The static load capacity  $C_0$  is the radially acting static load which does not cause any permanent deformation of the components when the spherical bearing or rod end is stationary, (i.e. the load condition without pivoting, swivelling or tilting movements).

It is also a precondition here that the operating temperature must be at normal room temperature and the surrounding components must possess sufficient stability.

The values specified in the tables are determined by static tension tests on a representative number of series components at 20°C normal room temperature. The static load capacity may vary with lower or higher temperature depending on the material.

In the case of all rod ends with plain bearings, the static load rating refers to the maximum permissible static load of the rod end housing in a tensile direction up to which no permanent deformation occurs at the weakest housing cross-section. The value in the product tables has a safety factor of 1.2 times the tensile strength of the rod ends housing material.

#### Static load capacity C<sub>0</sub> (roller and ball bearings)

For our rod ends with roller and ball bearings, the static load rating is the load at which the bearing can operate at room temperature without its performance being impaired as a result of deformations, fracture, or damage to the sliding contact surfaces (max  $1/10,000^{th}$  of the ball diameter).

#### Dynamic load capacity C (plain bearings)

Dynamic load ratings serve as values for calculation of the service life of dynamically-loaded spherical bearings and rod ends. The values themselves do not provide any information about the effective dynamic load capacity of the spherical bearing or rod end. To obtain this information, it is necessary to take into account the additional influencing factors such as load type, swivel or tilt angle, speed characteristic, max. permitted bearing clearance, max. permitted bearing friction, lubrication conditions and temperature, etc.

Dynamic load capacities depend on the definition used to calculate them. Comparison of values is not always possible owing to the different definitions used by various manufacturers, and because the load capacities are often determined under completely different test conditions.

#### Dynamic load capacity C (roller and ball bearings)

For our rod ends with roller and ball bearings, the dynamic load capacity is the load at which 90% of a large quantity of identical rod ends reach 1 million revolutions before they fail (due to fatigue of the rolling surfaces).







#### Low cost rod ends load ratings

The ultimate radial static load rating is measured as the failure point when a load is increasingly applied to a pin through the rod end's bore and pulled straight up while the rod end is held in place. Note that the actual rating is determined by calculating the lowest of the following three values:



2 Angle of 
$$\frac{T}{2}$$
 expressed in radians

3: Shank strength (S Value) male threaded rod end:

1: Raceway material comprehensive strength (R value):

### S = [(root diameter of thread<sup>2</sup> x .78) - (N<sup>2</sup> x .78)] x X

female threaded rod end:

### $S_2 = [(J^2 \times .78) + (major diameter of thread \times .78)] \times X$

Where: E = Ball diameter

- T = Housing width
- X = Allowable stress
- D = Head diameter
- N = Diameter of drilled hole in shank of male rod end
- J = Shank diameter of female rod end

The axial static load capacity is measured as the force required to cause failure via a load parallel to the axis of the bore. Depending on the material types and construction methods, the ultimate axial load is generally 10-20% of the ultimate radial static load. The formula does not account for the bending of the shank due to a moment of force, nor the strength of the stake in cartridge-type construction.

Axial strength (A Value):	
A = .78 [ (E + .176T) <sup>2</sup> - E2 ] x X	← ( ) ) >
Where: X = Allowable stress (see table below)	
E = Ball diameter	
T = Housing width	

Material	Allowable stress (PSI)			
300 Series Stainless Steel	35,000			
Low Carbon Steel	52,000			



ov-rod-ends-spherical-plain-bearings-lnh- Updated - 29-03-2023